

High Wall Cooling Only Ductless System

Indoor Model: DLFEHAA18XAK

Submittal Data

Job Data:

Location:

Buyer: Buyer P.O. #:


Carrier #:

Unit Number:

Model Number:

Performance Data Certified By:

Date:



STANDARD FEATURES

- Up-Down Louver control (fixed or swing)
- Remove filter from the top
- Improved serviceability with easy access to fan and electrical connections
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Quiet operation
- Aluminum Golden Hydrophilic pre-coated fins

Controls:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA

System	Size	18	
	Indoor Model	DLFEHAA18XAK	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	0	
	MCA	A.	0.4
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	° F (° C)	63~90 (17~32)
Piping	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	1/2 (12.7)

Indoor Coil	Face Area (sq. ft.)	Sq. Ft.	2.58
	No. Rows		2
	Fins per inch		20
	Circuits		2
Indoor	Unit Width	in (mm)	38.36 (974)
	Unit Height	in (mm)	12.8 (325)
	Unit Depth	in (mm)	8.87 (225)
	Net Weight	lbs (kg)	23.15 (10.5)
	Number of Fan Speeds		4
	Airflow (lowest to highest)	CFM	344/422/506/550
	Sound Pressure (lowest to highest)	dB(A)	34/39/43/45
	Air throw Data	ft (m)	24 (7.3)
	Moisture removal	Pint/h (L/h)	4.61 (2.18)
	Field Drain Pipe Size O.D.	in (mm)	0.625 (16)

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

For Compatibility See Product Data

Accessories

KSACN0401AAA	Wired Remote Control 7 day Programmable
KSAIF0101AAA	Wi-Fi™ Kit High Wall

