

# Floor Console Heat Pump Ductless System

Indoor Model: **DLFSFAH24XAK**

## Submittal Data

Job Data:  Location:

Buyer:  Buyer P.O. #:  Carrier #:

Unit Number:  Model Number:

Performance Data Certified By:  Date:



### STANDARD FEATURES

Modes: Cool, Heat, Dry, Fan, Auto  
 Timer  
 Auto-Restart  
 Sleep mode  
 Up-Down Louver control (fixed or swing)  
**Capable to be mounted on Floor and Ceiling**  
 Follow Me (Sense Temperature at handheld remote)  
 46°F Heating Mode (Heating Setback)  
 Aluminum Golden Hydrophilic pre-coated fins

### CONTROLS:

Wireless Remote Controller included with indoor unit  
 Optional Wired Remote Controller (Timer Function)  
 Optional Wired Remote Controller KSACN0501AAA (7 Day programmable)

System	Size	24	
	Indoor Model	DLFSFAH24XAK	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	1
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	62~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)

Indoor Coil	Face Area	Sq. Ft.	2.5
	No. Rows	3	
	Fins per inch	19	
	Circuits	7	
Indoor	Unit Width	in (mm)	42.05(1068)
	Unit Height	in (mm)	26.57(675)
	Unit Depth	in (mm)	9.25(235)
	Net Weight	lbs (kg)	58.42(26.5)
	Number of Fan Speeds	3	
	Airflow (lowest to highest)	CFM	600/710/760
	Sound Pressure (lowest to highest)	dB(A)	46/50/52
	Air throw Data	ft (m)	26 (8)
Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	

For Compatibility See Product Data

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

# Accessories

KSACN0101AAA	Wired Remote Control with Timer Function
KSACN0501AAA	Wired Remote Control 7 day Programmable
KSAIF0401AAA	Wi-Fi™ Kit Console

## Construction View Indoor Model: DLFSFAH24XAK

