

High Wall Heat Pump Ductless System

Indoor Model: DLFSHAH12XAK


Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto
- Turbo Mode
- Four fan speeds
- Sleep Mode
- Up-Down Louver control (fixed or swing)
- Follow Me (senses temperature at handheld remote)
- Heating Setback (46° F Heating Mode)
- Quiet indoor operation
- Aluminum Golden Hydrophilic pre-coated fins

CONTROLS:

- Wireless Remote Controller included with indoor unit
- Wired Remote Controller KSACN0101AAA (Optional)
- Wi-Fi™ Kit KSAIF0501AAA (Optional)

System	Size	12	
	Indoor Model	DLFSHAH12XAK	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	0.2
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	62~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	1/2 (12.7)

Indoor Coil	Face Area	Sq. Ft.	1.91
	No. Rows	2	
	Fins per inch	19	
	Circuits	2	
Indoor	Unit Width	in (mm)	31.89 (810)
	Unit Height	in (mm)	11.81 (300)
	Unit Depth	in (mm)	7.87 (200)
	Net Weight	lbs (kg)	18.3 (8.3)
	Number of Fan Speeds	4	
	Airflow (lowest to highest)	CFM	147/235/294/324
	Sound Pressure (lowest to highest)	dB(A)	26.1/33/41
	Air throw Data	ft (m)	22.93 (6.99)
Moisture removal	Pint/h (L/h)	3.2 (1.51)	
Field Drain Pipe Size O.D.	in (mm)	0.625 (16)	

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.
For Compatibility See Product Data

Accessories

KSACN0101AAA	Wired Remote Control with Timer Function
KSAIF0501AAA	Wi-Fi™ Kit High Wall Mid-Tier

Construction View

Indoor Model: **DLF SHAH12XAK**

